

HARVIA CILINDRO

HPCS6U1H

The Harvia Cilindro H electric heater has an outer casing that is partially open at the front, allowing users to enjoy the benefits of a large stone surface and place the heater containing a massive amount of stones in a small space. You can adjust between gentle and sharp steam by throwing water in the middle or on top of the stone pillar.



Features

Main material : Steel

H x W x D : 1010.0 x 360.0 x 340.0 mm

Net weight (kg) : 16.0


Installation location : Floor

| ID | GTIN | Output (kW) | Sauna room size min - max m3 |
|----------|---------------|-------------|------------------------------|
| HPCS6U1H | 6417659026208 | 6 kW | 4.0-8.0 |


Related products



HPC2




HPC3



SFE-D350



HPCU2L



HPCU3L



Spare parts

| Product | ID | Pcs |
|---|-----------|-----|
| Heating element 2000W/240V | Y10-0018 | 3 |
| Adjusting leg M10x60 | ZSA-442 | 1 |
| Adjusting leg M10x60 x 4 pcs, floor mounted heaters | SPZSA-442 | |

Technical details

| Technical data | Type / attribute | HPCS6U1H |
|------------------------------------|--|-----------------|
| | Color | Stainless Steel |
| | Power output | 6 kW |
| | Stone sizes | Ø5-10 cm |
| | Stone amount (kg) | 90 |
| | | |
| Dimensions | Product width | 360 |
| | Product height | 1010 |
| | Product depth (mm) | 340 |
| | Net weight (kg) | 16 |
| | Gross weight | 18 |
| | Package width | 1015 |
| | Package height | 375 |
| | Package depth | 375 |
| Safety and installation dimensions | Safety distance front (non-combustible materials) | 100 |
| | Safety distance side (non-combustible materials) | 30 |
| | Safety distance behind (non-combustible materials) | 30 |
| | Safety distance (Ceiling) | 890 |
| | Room min. height(depends on connections and therefore from output, star/delta) | 1900 |