



HARVIA VIRTÄ

HL9U1SA

The Virta Combi is a combined electric heater and steamer that provides a variety of sauna experiences. You can select between a traditional Finnish sauna, a steam sauna, a herbal sauna or an aromatic sauna.



Advantages

- The Virta Combi is a combined electric heater and steamer with sturdy structure for home sauna and professional use
- The large number of stones guarantees soft and abundant steam. Efficient air circulation heats the sauna very quickly
- Sleek and modern design
- The steamer is on the front behind the maintenance hatch
- The heating elements are separated from the stones, which results in a long heating element life span

Features

Main material : Steel


Net weight (kg) : 63.9

H x W x D : 33.0 x 16.0 x 16.0


Installation location : Floor

| ID | GTIN | Output (kW) | Sauna room size min - max m ³ |
|---------|---------------|-------------|--|
| HL9U1SA | 6417659020503 | 9 kW | 177.0-494.0 |

Related products



SFE-350400



HL1M



HL4



HL5



Spare parts

| Product | ID | Pcs |
|---|-----------|-----|
| Soapstone cup 0 46/36 | ZH-205 | 1 |
| H.elem.VirtaUSA3000W/240V,2250W/208V | Y10-0009 | |
| Adjusting leg M10x60 | ZSA-442 | 1 |
| | ZCU-997 | |
| Adjusting leg M10x60 x 4 pcs, floor mounted heaters | SPZSA-442 | |
| Soapstone cup Ø 46/36, grey | SPZH-205 | |

Technical details

| Technical data | Type / attribute | HL9U1SA |
|------------------------------------|--|----------|
| | Color | Black |
| | Power output | 9 kW |
| | Stone sizes | Ø5-10 cm |
| | Stone amount (kg) | 110 |
| Dimensions | Product width | 16 |
| | Product height | 33 |
| | Product depth (mm) | 16 |
| | Net weight (kg) | 63.9 |
| | Gross weight | 32.5 |
| | Package width | 500 |
| | Package depth | 500 |
| Safety and installation dimensions | Safety distance front (combustible materials) | 2 |
| | Safety distance right side (combustible materials) | 2 |
| | Safety distance left side (combustible materials) | 2 |
| | safety distance to the side wall (combustible materials) | 2 |
| | Safety distance behind (combustible materials) | 2 |
| | Safety distance (Ceiling) | 42 |
| | Room min. height(depends on connections and therefore from output, star/delta) | 75 |
| | Installation opening height | 1900 |
| | Installation opening width | 475 |
| | Installation opening depth | 470 |